

according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DEKAPHON 9735

UFI: CV5D-QMEC-X004-D2WU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76
Place: D-32676 Luegde

Telephone: + 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

e-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

butanone; ethyl methyl ketone

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9, aromatics

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 2 of 14

Precautionary statements

P103 Read carefully and follow all instructions.

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





Hazard statements

H222-H229-H412

Precautionary statements

P210-P211-P251-P410+P412

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 3 of 14

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)	·	
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, i	soalkanes, cyclics		15 - < 20 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox	. 1, Aquatic Chronic 2; H	225 H336 H304 H411	
78-93-3	butanone; ethyl methyl ketone			15 - < 20 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE	3; H225 H319 H336 EUF	1066	
74-98-6	propane			10 - < 15 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1A, Compressed gas; H	1220 H280		
106-97-8	n-butane	5 - < 10 %		
	203-448-7		01-2119474691-32	
	Flam. Gas 1A, Compressed gas; F			
	Hydrocarbons, C7, n-alkanes, isoa	1 - < 5 %		
	927-241-2	649-328-00-1	01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox	. 1, Aquatic Chronic 3; H	226 H336 H304 H412	
64742-95-6	Hydrocarbons, C9, aromatics	1 - < 5 %		
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE H411 EUH066	∃ 3, Asp. Tox. 1, Aquatic	Chronic 2; H226 H335 H336 H304	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, i	1 - < 5 %		
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc	Limits, M-factors and ATE			
64742-49-0	920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	15 - < 20 %		
	inhalation: LC	C50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg			
78-93-3	201-159-0	butanone; ethyl methyl ketone	15 - < 20 %		
	dermal: LD50) = 6480 mg/kg; oral: LD50 = 2740 mg/kg			
	927-241-2	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	1 - < 5 %		
	inhalation: LC mg/kg	C50 = 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 4951			
64742-95-6	918-668-5	Hydrocarbons, C9, aromatics	1 - < 5 %		
	dermal: LD50) = >3160 mg/kg; oral: LD50 = 3492 mg/kg			
64742-49-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	1 - < 5 %		
	dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg				

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

SECTION 4: First aid measures



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 4 of 14

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

Wash with plenty of water/Soap. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use appropriate respiratory protection.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 5 of 14

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Provide adequate ventilation.

Clear contaminated areas thoroughly.

Do not rinse down with water.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

No further relevant information available.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 6 of 14

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³
Consumer DN	EL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
64742-95-6	Hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	150 mg/m³
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m³
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Recommended glove articles

FKM (fluoro rubber), Breakthrough time:: 480 min. NBR (Nitrile rubber), Breakthrough time:: 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 7 of 14

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141)., Filter material/medium: A

short-term Filter material/medium : A1/P1 long-term Filter material/medium : A1/P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol Colour: black

Odour: characteristic
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

-42 °C

boiling range: Flammability

Solid/liquid: not determined
Gas: not determined
Lower explosion limits: 0,6 vol. %
Upper explosion limits: 11,5 vol. %

Flash point: < -20 °C DIN 53213

Auto-ignition temperature: > 200 °C
Decomposition temperature: not determined
pH-Value: not determined
Viscosity / kinematic: not determined
Water solubility: not applicable

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 8300 hPa

(at 20 °C)

Density (at 20 °C): 0,82 g/cm³ DIN 51757

Relative vapour density: not determined Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties not determined

Sustaining combustion: No data available

Self-ignition temperature

Solid: not determined Gas: not determined

Oxidizing properties not determined

Other safety characteristics

Solvent content: 65,1 % Solid content: 35,2 %



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 8 of 14

Softening point: not determined Viscosity / dynamic: not determined

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 9 of 14

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics							
	oral	LD50 mg/kg	>5000	Rat				
	dermal	LD50 mg/kg	>2000	Rabbit				
	inhalation (4 h) vapour	LC50	>20 mg/l	Rat				
78-93-3	butanone; ethyl methyl ke	etone						
	oral	LD50 mg/kg	2740	Rat				
	dermal	LD50 mg/kg	6480	Rabbit				
	Hydrocarbons, C7, n-alka	anes, isoalka	nes, cyclics					
	oral	LD50 mg/kg	4951	Rat				
	dermal	LD50 mg/kg	> 5000	Rat				
	inhalation (4 h) vapour	LC50	4951 mg/l	Rat				
64742-95-6	Hydrocarbons, C9, aroma	atics						
	oral	LD50 mg/kg	3492	Rat				
	dermal	LD50 mg/kg	>3160	Rabbit				
64742-49-0	Hydrocarbons, C6-C7, n-	alkanes, iso	alkanes, cycl	ics, <5% n-hexane				
	oral	LD50 mg/kg	>5000	4				
	dermal	LD50 mg/kg	>5000	7				

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; butanone; ethyl methyl ketone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Print date: 09.01.2023



Safety Data Sheet

according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 10 of 14

Practical experience

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting potential No information available.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
64742-49-0	Hydrocarbons, C7-C9, n-a	ılkanes, iso	alkanes, cycl	ics				
	Acute fish toxicity	LC50 mg/l	1-10	96 h	fish			
	Acute crustacea toxicity	EC50 mg/l	1-10		Daphnia magna (Big water flea)			
64742-95-6	Hydrocarbons, C9, aromatics							
	Acute fish toxicity	LC50	9,2 mg/l		Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50	2,9 mg/l		Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50	3,2 mg/l		Daphnia magna (Big water flea)			

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-93-3	butanone; ethyl methyl ketone	0,29
74-98-6	propane	2,36

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 11 of 14

Disposal recommendations

Dispose of waste according to applicable legislation.

Do not mix with other wastes.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 12 of 14



Marine pollutant:

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

 14.3. Transport hazard class(es):
 2.1

 14.4. Packing group:

 Hazard label:
 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: gas

Other applicable information

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from" class

1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class

2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class

2.

Category C, Clear of living quarters.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 29, Entry 40, Entry 75



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 13 of 14

2004/42/EC (VOC): 63,87 % 524,4 g/l

Information according to 2012/18/EU

(SEVESO III):

P3a FLAMMABLE AEROSOLS

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

oldedinedien for mixtures and deed evaluation method describing to ob our regulation						
Classification	Classification procedure					
Aerosol 1; H222-H229	On basis of test data					
Eye Irrit. 2; H319	Bridging principle "Aerosols"					
STOT SE 3; H336	Bridging principle "Aerosols"					
Aquatic Chronic 3; H412	Calculation method					

Relevant H and EUH statements (number and full text)

11220	Extremely naminable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Extremely flammable das

H220



according to UK REACH Regulation

DEKAPHON 9735

Revision date: 09.01.2023 Product code: 217072 Page 14 of 14

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)